



HX 胶带

东莞市海翔胶粘制品有限公司

DONGGUAN HAIXIANG ADHESIVE PRODUCTS CO., LTD (branch)
Factory address: The Industrial Zone of Bajiao wo su wu in Wanjiang area, Dong guan City, Guangdong Province, China

TEL: +86 769-38818885 **FAX:** +86 769-89280809

Website: <http://www.tapemanufacture.com>

350mic 地毯双面胶带物理性能检验报告

(350mic Double sided carpet tape physical performance test sheet)

序号 (No.)	项目(Item)	单位 (Unit)	检测标准(Test Standard)	检验方法 (Test way)	测试数据 (Technical Data)	
1	外观 (appearance)	\	胶粘带呈卷状，表面平整，色泽均匀，两侧平齐无折痕，溢胶色斑显著变形等缺陷。 (our tape is per roll, tidy surface, uniform colour, two sides is tidy, not fold, and stain and so on defect.	目测 (visual test)	\	
2	解卷剥离 (stripping)	\	不允许有胶粘剂脱落或迁移至下层离型纸背面(Don't allow glue to drop or move to the reverse side of release paper)	GB-4850-198 4	\	
3	厚度 (Thickness)	mm	0.35±0.05	\	0.35	
4	涂胶宽度 (Glue width)	mm	≥1020	\	1020	
5	初粘 (Initial tack)	内	钢球号 (#) (Ball No.)	≥18	GB-4852-198 4	32
		外				32
6	持粘性 (Permanent adhesion)	内	H/25mm	≥1.0	GB-4851-199 8	4
		外				5
7	180 剥离 强度 (peel strength)	内	N/25mm	≥20	GB-2792-198 8	34.3
		外				32.3
8	测试条件 (Test condition)	温度 23±2° C 相对湿度 65±5° C Temperature 23±2° C relative temperature 65±5° C				